

定格及び寸法

\* RDシリーズ(丸形金属ケース)

| 定格電圧<br>(V.AC) | 静電容量範囲<br>( $\mu$ F) | 各部寸法(mm) |    |     |     |  | ケース呼称   |
|----------------|----------------------|----------|----|-----|-----|--|---------|
|                |                      | A        | B  | H   | L   |  |         |
| 220            | ~60                  | 48       | 45 | 76  | 87  |  | G45-75  |
|                | 61~72                | 48       | 45 | 96  | 107 |  | G45-95  |
|                | 73~76                | 53       | 50 | 76  | 87  |  | G50-75  |
|                | 77~93                | 53       | 50 | 96  | 107 |  | G50-95  |
|                | 94~125               | 48       | 45 | 126 | 137 |  | G45-125 |
|                | 126~150              | 54       | 51 | 126 | 137 |  | G51-125 |
| 275            | ~38                  | 48       | 45 | 76  | 87  |  | G45-75  |
|                | 39~49                | 53       | 50 | 76  | 87  |  | G50-75  |
|                | 50~59                | 53       | 50 | 96  | 107 |  | G50-95  |
| 330            | ~26                  | 48       | 45 | 76  | 87  |  | G45-75  |
|                | 27~38                | 48       | 45 | 96  | 107 |  | G45-95  |
|                | 39~49                | 53       | 50 | 96  | 107 |  | G50-95  |
| 440            | ~14                  | 48       | 45 | 76  | 87  |  | G45-75  |
|                | 15~19                | 53       | 50 | 76  | 87  |  | G50-75  |
|                | 30~31                | 48       | 45 | 126 | 137 |  | G45-125 |
|                | 32~40                | 54       | 51 | 126 | 137 |  | G51-125 |
|                | 41~61                | 63       | 60 | 123 | 136 |  | G60-122 |
| 480            | ~11.5                | 48       | 45 | 76  | 87  |  | G45-75  |
|                | 12~15                | 53       | 50 | 76  | 87  |  | G50-75  |
|                | 16~24                | 48       | 45 | 126 | 137 |  | G45-125 |
|                | 25~31.5              | 54       | 51 | 126 | 137 |  | G51-125 |
|                | 32~48                | 63       | 60 | 123 | 136 |  | G60-122 |
| 550            | ~7.5                 | 48       | 45 | 76  | 87  |  | G45-75  |
|                | 8~9.5                | 53       | 50 | 76  | 87  |  | G50-75  |
|                | 10~13                | 48       | 45 | 96  | 107 |  | G45-95  |
|                | 14~16.5              | 53       | 50 | 96  | 107 |  | G50-95  |
|                | 17~19                | 48       | 45 | 126 | 137 |  | G45-125 |
|                | 20~24.5              | 54       | 51 | 126 | 137 |  | G51-125 |
|                | 25~37.5              | 63       | 60 | 123 | 136 |  | G60-122 |